

The following items have been taken from R&D progress reports of the Technical Services and Support Group and are being distributed because of their general interest. We would like to know what questions or problems you have concerning the items reported in this edition. Your comments concerning related R&D topics will also be appreciated. A form is attached that will make it more convenient for you to submit your comments. An effort will be made to answer them either personally or in future R&D News Notes.

Mensuration Instrument for PIs

25)

high precision equipment wand tube magnifiers used be Line PI Comparator under of the PI to quickly make relecontract requires the desidevice that will utilize metalled be about 34 by 48 incompared by 48 incomp	der development will bridge ased by the photogrammetrist by the photo interpreter. The contract with the atively accurate measurement and fabrication of a commodified High Power options in size and is intended ave two 6-inch square viewing the for film chips. The PI are the stereo images need will be equipped with a dia variable differential drimparator will be on line with accuracy of two microns over will allow the PI to fulfill self and allow the photogram atty requirements. The Projective will requirements.	and the scales he Twin Stage On will allow ts. The one year pact, light weight cs. The equipment to be used in the g stages to accommo- will be able to per- not have the same fferential mag- ve to compensate for h NPIC's Univac 494 r a one inch area. l the majority of metrist to concen-
equipment is	Room 5S-453B). The work is
classified	1	,
	J	C DOUB 4
WARNING THIS DOCUMENT IS FOR USE BY U.S.	1	GROUP 1 EXCLUDED FROM AUTOMATIC
GOVERNMENT PERSONNEL ONLY. COM-		DOWNGRADING AND DECLASSIFICATION
MERCIAL INTERESTS CANNOT REVIEW OR		1000


<u>ᢀᢐᡏᠷ៲៷ͺͼϙϧͱͼϪϼϧͱϧϭϧͼϻͺϧϧϧͺ</u>Release 2005/02**%[デር]ℝ∄Ϫ**-RDP78B047**ֈԾ֎֎֍֍ֈ֎֍ֈ֎֍ֈ֎֍ֈ**֎ֈֈ֎ֈֈֈ

Approved For Release 2005/025FCRFTA-RDP78B04770A001300030009-7

News Images From Old


One of the most spectacular and potentially rewarding developments in photography has reached a new milestone. An advanced computer processing technique called Digital Image Restoration has demonstrated that it can extract recognizable imagery from extremely degraded photographs. The blurred photograph shown below is typical of low quality or degraded imagery acquired in the presence of atmospheric disturbances (smog or haze), camera malfunction or film graininess. The Exploratory Laboratory, working with its contractor, processed the image as shown in the succeeding photograph. Briefly, this is how Digital Image Restoration works.


Using a light-sensitive electronic detector, darkness values are read from small areas of degraded film. Values are obtained in the form of a mosaic of 64×64 tiny squares. The darkness value for each tiny square depends upon the density or degree of imagery darkness originally recorded.





PARTIALLY RESTORED IMAGE





POSITIVE OF RESTORED NEGATIVE IMAGE

RESTORED NEGATIVE IMAGE

Approved For Release 2005/02**ታ፫ር የደረ**ተ-RDP78B04770A001300030009-7

Darkness values are electronically translated into a form that is understood by an IBM 1800 computer and presented to it. The computer is instructed to produce preliminary data on the scene. From this data the scientist estimates the amount of detail in the scene, and he directs the computer to apply one of a series of correction operations to the darkness values. This essentially minimizes the effects of degrading factors. Finally, the computer is directed to present the "clear" imagery on Polaroid film in the original 64 x 64 mosaic form, each mosaic element 1/32" x 1/32" in size. The current program phase was intended to demonstrate feasibility. This accomplished, the Laboratory plans a continuous effort to yield a practical system. It ultimately envisions hardware which will serve as a new PI tool for exploiting degraded imagery of the future. The Project Monitor is	25
Scarcity of Silver Prompts New Research	
Silver has become an increasingly important commodity in our economy. Industrial consumption in 1964 was 127 million ounces, 31 percent of which was used by the photographic industry. However, the extreme scarcity of this valuable metal has doubled its price in the past two years. It is now valued at \$2.40 per troy ounce while U.S. production is only 25 percent of industrial requirements. In an effort to conserve silver, NPIC has been examining several approaches to develop non-silver photographic materials. One of these approaches involves a relatively new science (about 6 years old), known as Light Excited Chemistry	
achieved by applying heat. A study by	25
Room 5S 453H) contains a brief explanation of the new science, compares	
the Free-Radical materials with silver and other materials, and evaluates	
the work done by This article is	25
Learning More About Anamorphic Eyepieces	
A recent report written by describes in detail a method for obtaining optimum stereo fusion using the Compact Variable Anamorphic Eyepieces. The report, classified SECRET, is entitled Procedures for Setting up Anamorphic Eyepieces and is dated 25 January 1968. While the report was widely distributed shortly after its publication, you may have inadvertently missed this valuable information. Additional copies can be obtained	25

25)

from the Development & Engineering Division of TSSG.

Approved For Release 2005/02577 RFTA-RDP78B04770A001300030009-7

Understanding R&D

In response to questions concerning research and development, this issue and future issues will contain brief articles covering the nature of R&D or concerning some of the terms often used in modern technical writings. The subject of this issue is a discussion of the sequence of events occurring prior to actual development work.

Before the development of new equipment can begin, four prerequisites must be accomplished. First, the need for the equipment must be recognized and defined. Present equipment may be inadequate because it is too slow, does not produce accurate or sufficient output, is not adequate for an oncoming collection system, is uneconomical to use, or for other reasons. Once the need is defined, the market must be examined to determine if "off-the-shelf", or previously developed, commercially available equipment will meet the need. If such equipment can be purchased then there is no need for a development. The non-existence of adequate equipment logically leads to the third prerequisite; the matching of the need with the state-of-the-art. In other words, we must review recent research and development in those fields of science and engineering related to the defined needs to determine how close they come to solving the problem. This is done by consulting with industrial and governmental R&D organizations, by reading technical journals and by performing patent searches.

The three prerequisites may not be accomplished in the exact sequence just described. Occasionally, a review of the state-of-the-art may reveal a new process or piece of equipment that leads to the realization that present procedures or equipment can be improved considerably with some additional development. This reviewing process usually discloses those organizations (companies, laboratories, universities, etc.) that have done work in the area of interest and may be prospective contractors for the development.

After these three prerequisites have been satisfactorily accomplished administrative approval must be obtained and funds allocated for the work. The higher the cost of the proposed project, the higher the authorization required for its approval.

+25)

Approved For Release 2005/02/17: GIA-RDP78B04770A001300030009-7

R&D NEWS NOTES
(Date) TO: Editor, <u>R&D NEWS NOTES</u> , TSSG/DED FROM:
I would like to offer my comments/questions concerning some of the following items. a. Mensuration Instrument for PI's
b. New Images From Old
c. Scarcity of Silver Prompts New Research
d. Learning More About Anamorphic Eyepieces
e. Understanding R&D